

# INSTANT

With constant quality, high-value performance and good service **DINGLI** wins the trust of customers and enjoys a good reputation in the market. The **DINGLI** brand provides a full range of areal work platforms and carries forward the great spirit of innovation, customer dedication and good old-fashioned hard work. These qualities have made the Dingli name synonymous with quality and reliability worldwide.

The **INSTANT** brand has been known in the market for more than 30 years. The leading rental shops, large government agencies as well as a vast number of entrepreneurs and contractors are among our faithful and satisfied customers. Our main objective will always be to deliver quality products at reasonable prices, as we know that quality is essential for safe and secure operations.

#### Norway

Tel.: +47 23 19 11 00  
info@instant.no

#### Lithuania

Tel.: +370 5 233 1096  
info@instant.lt

#### Latvia

Tel.: +371 263 58 152  
info@instantlatvija.lv

#### Estonia

Tel.: +372 680 76 33  
info@instant.ee

[www.dingli.eu](http://www.dingli.eu)



#### SCISSOR LIFTS

JCPT3.0(III)  
JCPT0807DC  
JCPT(mini) JCPT3.0 / JCPT 3.9  
JCPT1008HD  
JCPT1012HD  
JCPT1017CRT / JCPT1217CRT  
JCPT1212HD  
JCPT1013OD / JCPT1213OD  
JCPT1223RT / JCPT1523RT / JCPT1823RT

#### MAST LIFTS

AMWP6-1000 / AMWP7.5-1000  
ZDYT3-4.5  
EGTWY6.5-1000 / EGTWY8-1000

#### BOOM LIFTS

GTBZ16A  
GTBZ14S / GTBZ16S  
GTBZ26S / GTBZ28S  
GTBZ32S / GTBZ34S  
GTBZ36S / GTBZ38S  
GTBZ40S / GTBZ42S

 **Dingli**  
Machinery

Product range overview

self drive

## Dingli JCPT3.0(III)



max. working height	5,00 m
platform capacity (SWL)	240 kg
overall height	1,82 m
overall length	1,18 m
overall width	0,76 m
gross weight	495 kg



Dingli scissor lift **JCPT3.0(III)** with a working height of 5 m and platform size of 0,6 x 1,17 m comes with non - marking tires. The JCPT3.0(III) model has a width of 0,76 m stowed and can easily go through a normal doorway.

## Dingli JCPT0807DC



max. working height	7,80 m
platform capacity (SWL)	230 kg
overall height (rails up/down)	2,16/1,84 m
overall length	1,86 m
overall width	0,76 m
gross weight	1240 kg



Dingli **JCPT0807DC** proposes a working height of up to 7,8 m and has a platform capacity of 230 kg. The lift is compact and nimble and has an outside turning radius of less than 1,64 m. In addition, it can climb slopes of up to 25 degrees.

## Dingli JCPT1008HD



max. working height	10,0 m
platform capacity (SWL)	230 kg
overall height (rails up/down)	2,34/1,88 m
overall length	2,48 m
overall width	0,81 m
gross weight	2100 kg



Dingli **JCPT1008HD** is designed for indoor construction and maintenance tasks. This model offers a working height up to 10 m and the width is 0,81 m specialized for confined spaces. Even though the machine is mostly for indoor use, it can be used outdoor as well.

## Dingli JCPT1012HD



max. working height	10,0 m
platform capacity (SWL)	450 kg
overall height (rails up/down)	2,34/1,86 m
overall length	2,48 m
overall width	1,15 m
gross weight	2300 kg



Dingli **JCPT1012HD** is designed for indoor construction and maintenance tasks. The electric scissor lift offers a working height up to 10 m with a 1,15 m width when more working area is required. The machine can be used outdoors as well.

## Dingli JCPT1212HD



max. working height	12,0 m
platform capacity (SWL)	320 kg
overall height (rails up/down)	2,47/1,99 m
overall length	2,48 m
overall width	1,15 m
gross weight	2730 kg



Dingli **JCPT1212HD** is designed for indoor construction and maintenance tasks. The electric scissor lift offers a working height up to 12 m with a 1,15 m width when more working area and height is required. The machine can be used outdoors as well.

## Dingli JCPT1013OD / JCPT1213OD



max. working height	10,0 m	12,0 m
platform capacity (SWL)	450 kg	400 kg
overall height	2,45 m	2,45 m
overall length	2,51 m	2,51 m
overall width	1,30 m	1,30 m
gross weight	2500 kg	2550 kg



Dingli **JCPT1013(OD) / JCPT1213(OD)** mobility is provided with a very unique Omni-directional undercarriage allowing the lift to move in any direction. This provides maneuverability in a tight spot and enables a precise positioning in places that are hard to reach.

push-around

## Dingli JCPT(mini) JCPT3.0 / JCPT 3.9



max. working height	5,00 m	5,90 m
platform capacity (SWL)	240 kg	240 kg
overall height	1,78 m	1,86 m
overall length	1,15 m	1,15 m
overall width	0,70 m	0,70 m
gross weight	366 kg	420 kg



Dingli JCPT (mini) is a small, manually operated push-around scissor lift that is very easy to maneuver. The lift has a safe working height of up to 5/5,9 m more over compact size which ensures a fast and easy transportation.

rough terrain

## Dingli JCPT1017CRT / JCPT1217CRT



max. working height	10,0 m	12,0 m
platform capacity (SWL)	567 kg	454 kg
overall height (rails up/down)	2,32/1,70 m	2,45/1,83 m
overall length	2,67 m	2,67 m
overall width	1,73 m	1,73 m
gross weight	3222 kg	4098 kg



The lightweight and compact Dingli JCPT1017RT / JCPT1217RT scissor lifts are ideal for outdoor work in confined spaces between buildings. They have excellent ground clearance of 0,19 m and turning radius inside/outside of 1,52/3,68 m.

## Dingli JCPT1223RT / JCPT1523RT / JCPT1823RT



max. working height	12,0 m	15,0 m	18,0 m
platform capacity (SWL)	1000 kg	680 kg	680 kg
overall height	2,76 m	2,98 m	3,15 m
overall length	4,88 m	4,88 m	4,88 m
overall width	2,27 m	2,27 m	2,27 m
gross weight	7300 kg	7800 kg	8700 kg



JCPT1223RT / JCPT1523RT / JCPT1823RT are engineered for max. performance on construction. The spacious 6,57 x 1,83 m deck can lift up to 1000 kg. Standard features include twin deck extensions, powerful 4 wheel drive and oscillating axles.

self drive

## Dingli AMWP6-1000 / AMWP7.5-1000



max. working height	8,00 m	9,50 m
platform capacity (SWL)	150 kg	125 kg
overall height	1,98 m	1,98 m
overall length	1,36 m	1,36 m
overall width	0,79 m	0,79 m
gross weight	850 kg	880 kg



AMWP series lifts are perfect for working in confined spaces, with skid steer and a zero inside turning circle. The weight is just 850/880 kg and the lifts deliver a working height of 8,0/9,5 m and can lift 150/125 kg.

## Dingli ZDYT3-4.5



max. working height	6,50 m
platform capacity (SWL)	300 kg
overall height	1,98 m
overall length	1,53 m
overall width	0,70 m
gross weight	675 kg



Dingli ZDYT3-4.5 pick and place with ease - a great solution for your inventory stocking needs. The lift has a small working envelope for maneuvering around corners, and in addition, a tight turning radius perfect for narrow aisle ways.

manual

## Dingli EGTWY6.5-1000 / EGTWY8-1000



max. working height	8,50 m	10,0 m
platform capacity (SWL)	125 kg	125 kg
overall height	1,98 m	1,98 m
overall length	1,20 m	1,20 m
overall width	0,69 m	0,69 m
gross weight (AC/DC)	310/365 kg	340/390 kg



EGTWY series lift is an affordable and efficient push around mast lift that is easy to use and easy to maintain. It is compact and light weighted, and can easily be maneuvered.

### Dingli GTBZ16A



max. working height	16,0 m	
platform capacity (SWL)	230 kg	
overall height	2,33 m	
overall length	6,94 m	
overall width	2,30 m	
gross weight	7500 kg	



Dingli **GTBZ16A** is articulated boom lift with great up and over performance with a working height of 16 m and an outreach of 7,47 m. The GTBZ16A model is very compact, giving it an advantage compared to the other products in the range. Perkins engine delivers impressive performance with low operating costs.

### Dingli GTBZ14S / GTBZ16S



max. working height	14,0 m	16,0 m
platform capacity (SWL)	230 kg	230 kg
overall height	2,55 m	2,55 m
overall length	7,40 m	8,41 m
overall width	2,30 m	2,30 m
gross weight	6500 kg	6750 kg



The self propelled telescopic stick boom lifts Dingli **GTBZ14S / GTBZ16S** have a working height from 14/16 m and an outreach from 9,65/11,6 m. The machines are robust and have an outstanding performance for versatile use. They are delivered with Perkins engine.

### Dingli GTBZ26S / GTBZ28S



max. working height	26,0 m	28,0 m
platform capacity (SWL)	230 kg	230 kg
overall height	3,07 m	3,07 m
overall length	11,2 m	12,5 m
overall width (axle extended)	3,35 m	3,35m
gross weight	18000 kg	18150 kg



The self propelled telescopic stick boom lifts Dingli **GTBZ26S / GTBZ28S** have a working height from 26/28 m and an outreach from 21/22,5 m. The machines are robust and have an outstanding performance for versatile use. They are delivered with Perkins engine.

### Dingli GTBZ32S / GTBZ34S



max. working height	32,0 m	34,0 m
platform capacity (SWL)	340 kg	230 kg
overall height	3,07 m	3,07 m
overall length	12,0 m	13,5 m
overall width (axle extended)	3,35 m	3,35 m
gross weight	18150 kg	19000 kg



The self propelled telescopic stick boom lifts Dingli **GTBZ32S / GTBZ34S** have a working height from 32/34 m and an outreach from 21/22,5 m. The machines are robust and have an outstanding performance for versatile use. They are delivered with Perkins engine.

### Dingli GTBZ36S/GTBZ38S



max. working height	36,0 m	38,0 m
platform capacity (SWL)	340 kg	230 kg
overall height	3,07 m	3,07 m
overall length	13,0 m	14,25 m
overall width (axle extended)	3,80 m	3,80 m
gross weight	19500 kg	19850 kg



The self propelled telescopic stick boom lifts Dingli **GTBZ36S / GTBZ38S** have a working height from 36/38 m and an outreach from 22/24,2 m. The machines are robust and have an outstanding performance for versatile use. They are delivered with Perkins engine.

### Dingli GTBZ40S/GTBZ42S



max. working height	40,0 m	42,0 m
platform capacity (SWL)	340 kg	230 kg
overall height	3,07 m	3,07 m
overall length	13,0 m	14,25 m
overall width (axle extended)	3,80 m	3,80 m
gross weight	20400 kg	20560 kg



The self propelled telescopic stick boom lifts Dingli **GTBZ40S / GTBZ42S** have a working height from 40/42 m and an outreach from 22,1/24,2 m. The machines are robust and have an outstanding performance for versatile use. They are delivered with Perkins engine.